

Hengetr dler i cm. med utliggerh yde = 210 cm.

Lengden av hengetr. angir avst. fra center av b erekabel til center av kontakttr d.

Spenn (m)	Nedh. av kt. i cm.	Antall hengetr.	I	II	III	IV	Spenn (m)	Nedh. av kt. i cm.	Antall hengetr.	I	II
62	10.7	4	(12.4) 117	(24.8) 71	(37.2) 71	(49.6) 117	36	3.6	2	(12.0) 167	(24.0) 167
61	10.3	"	(12.2) 120	(24.4) 75	(36.6) 75	(48.8) 120	35	3.4	"	(11.66) 169	(23.32) 169
60	10.0	"	(12.0) 123	(24.0) 80	(36.0) 80	(48.0) 123	34	3.2	"	(11.33) 171	(22.66) 171
59	9.7	"	(11.8) 126	(23.6) 84	(35.4) 84	(47.2) 126	33	3.0	"	(11.0) 173	(22.0) 173
58	9.3	"	(11.6) 129	(23.2) 88	(34.8) 88	(46.4) 129	32	2.8	"	(10.66) 175	(21.32) 175
57	9.0	"	(11.4) 131	(22.8) 92	(34.2) 92	(45.6) 131	31	2.7	"	(10.33) 177	(20.66) 177
56	8.7	"	(11.2) 134	(22.4) 96	(33.6) 96	(44.8) 134	30	2.5	"	(10.0) 180	(20.0) 180
55	8.4	"	(11.0) 137	(22.0) 100	(33.0) 100	(44.0) 137	29	2.3	"	(9.66) 182	(19.32) 182
54	8.1	"	(10.8) 139	(21.6) 104	(32.4) 104	(43.2) 139	28	2.2	"	(9.33) 183	(18.66) 183
53	7.8	"	(10.6) 142	(21.2) 108	(31.8) 108	(42.4) 142	27	2.0	"	(9.0) 185	(18.0) 185
52	7.5	"	(10.4) 144	(20.8) 111	(31.2) 111	(41.6) 144	26	1.9	"	(8.66) 187	(17.32) 187
51	7.2	"	(10.2) 147	(20.4) 115	(30.6) 115	(40.8) 147	25	1.7	2	(8.33) 189	(16.66) 189
50	6.9	"	(10.0) 149	(20.0) 119	(30.0) 119	(40.0) 149	24	1.6	1	(12.0) 188	
49	6.7	4	(9.8) 152	(19.6) 122	(29.4) 122	(39.2) 152	23	1.5	"	(11.5) 190	
48	6.4	3	(12.0) 145	(24.0) 123	(36.0) 145		22	1.4	"	(11.0) 192	
47	6.1	"	(11.75) 147	(23.5) 126	(35.25) 147		21	1.2	"	(10.5) 193	
46	5.9	"	(11.5) 150	(23.0) 130	(34.5) 150		20	1.1	"	(10.0) 194	
45	5.6	"	(11.25) 153	(22.5) 133	(33.75) 153		19	1.0	"	(9.5) 196	
44	5.4	"	(11.0) 155	(22.0) 136	(33.0) 155		18	0.9	"	(9.0) 197	
43	5.1	"	(10.75) 157	(21.5) 140	(32.25) 157		17	0.8	"	(8.5) 199	
42	4.9	"	(10.5) 160	(21.0) 143	(31.5) 160		16	0.7	"	(8.0) 200	
41	4.7	"	(10.25) 162	(20.5) 146	(30.75) 162		15	0.6	"	(7.5) 201	
40	4.5	"	(10.0) 164	(20.0) 149	(30.0) 164		14	0.5	"	(7.0) 202	
39	4.2	"	(9.75) 167	(19.5) 152	(29.25) 167		13	0.5	1	(6.5) 203	
38	4.0	"	(9.5) 169	(19.0) 155	(28.5) 169						
37	3.8	3	(9.25) 171	(18.5) 158	(27.75) 171						

Lengden av hengetr. 1,5 m. fra  kmidt. Ved typene  na,  sa og  va tilpasses. Tallene i parentes angir avstand i meter fra en av utliggerne til hver enkelt hengetr d ved de forskjellige spennlengder.

Tabellen er gyldig for: 100<sup>a</sup> kt, 50<sup>a</sup> bk, og strekk i kt: HK = 742 kg., strekk i bk: H<sub>B</sub> = 371 kg., og 10 cm. max. nedheng p  kt ved 60 m. spenn.