

Hengetr d lengder i cm.  
med en utliggerh yde = 1,80 m.

Lengen av hengetr d angir avst. fra senter av b rekabel til senter av kontakttr d.

Spenn m.		Antall hengetr.	1	2	3	4	Spenn m.		Antall hengetr.	1	2
60	10,0	4	(12,0) *) 95	(24,0) 53	(36,0) 53	(48,0) 95	36	3,6	2	(12,0) 138	(24,0) 138
59	9,7	"	(11,8) 98	(23,6) 57	(35,4) 57	(47,2) 98	35	3,4	"	(11,66) 140	(23,32) 140
58	9,3	"	(11,6) 101	(23,2) 61	(34,8) 61	(46,4) 101	34	3,2	"	(11,33) 142	(22,66) 142
57	9,0	"	(11,4) 103	(22,8) 65	(34,2) 65	(45,6) 103	33	3,0	"	(11,0) 144	(22,0) 144
56	8,7	"	(11,2) 106	(22,4) 69	(33,6) 69	(44,8) 106	32	2,8	"	(10,66) 146	(21,32) 146
55	8,4	"	(11,0) 109	(22,0) 73	(33,0) 73	(44,0) 109	31	2,7	"	(10,33) 148	(20,66) 148
54	8,1	"	(10,8) 111	(21,6) 76	(32,4) 76	(43,2) 111	30	2,5	"	(10,0) 150	(20,0) 150
53	7,8	"	(10,6) 114	(21,2) 81	(31,8) 81	(42,4) 114	29	2,3	"	(9,66) 152	(19,32) 152
52	7,5	"	(10,4) 116	(20,8) 84	(31,2) 84	(41,6) 116	28	2,2	"	(9,33) 154	(18,66) 154
51	7,2	"	(10,2) 118	(20,4) 87	(30,6) 87	(40,8) 118	27	2,0	"	(9,0) 156	(18,0) 156
50	6,9	"	(10,0) 121	(20,0) 91	(30,0) 91	(40,0) 121	26	1,9	"	(8,66) 158	(17,32) 158
49	6,7	"	(9,8) 123	(19,6) 95	(29,4) 95	(39,2) 123	25	1,7	"	(8,33) 159	(16,66) 159
48	6,4	3	(12,0) 116	(24,0) 95	(36,0) 116		24	1,6	1	(12,0) 159	
47	6,1	"	(11,75) 119	(23,50) 98	(35,25) 119		23	1,5	"	(11,5) 161	
46	5,9	"	(11,50) 121	(23,0) 102	(34,5) 121		22	1,4	"	(11,0) 162	
45	5,6	"	(11,25) 124	(22,5) 105	(33,75) 124		21	1,2	"	(10,5) 164	
44	5,4	"	(11,0) 126	(22,0) 109	(33,0) 126		20	1,1	"	(10,0) 165	
43	5,1	"	(10,75) 129	(21,50) 111	(32,25) 129		19	1,0	"	(9,5) 167	
42	4,9	"	(10,5) 131	(21,0) 115	(31,5) 131		18	0,9	"	(9,0) 168	
41	4,7	"	(10,25) 133	(20,50) 118	(30,75) 133		17	0,8	"	(8,5) 169	
40	4,5	"	(10,0) 136	(20,0) 121	(30,0) 136		16	0,7	"	(8,0) 170	
39	4,2	"	(9,75) 138	(19,5) 124	(29,25) 138		15	0,6	"	(7,5) 172	
38	4,0	"	(9,5) 140	(19,0) 126	(28,5) 140		14	0,5	"	(7,0) 173	
37	3,8	"	(9,25) 142	(18,5) 129	(27,75) 142		13	0,5	"	(6,5) 174	

Lengden av hengetr. 1,5m fra utlig.type 1/ tilpasses.

\*) Tallene i parentes angir avst. i m. fra en av utliggerne til hver enkelt hengetr. ved de forskjellige spennlengder.  
Tabellen er gyldig for HB = 333 kg, og HK = 667 kg. med 10 cm. max. nedheng p  KT. ved 60 m. spenn BK. = 50 mm<sup>2</sup> Cu KT = 100mm<sup>2</sup> Cu.

r1 Kongsberg 26/6 -35  
sign KH